



AKUREYRI AIRPORT — INTERNATIONAL GATEWAY

Akureyri International Airport has one runway which is 2,400 m long, 45 m wide and can safely accommodate the largest airplanes. The airport is controlled by highly qualified air traffic controllers (ATC). The approach control equipment and lighting system are up to the highest standards and include LOC, ILS and GPS approaches.

The fire and rescue service at the airport is in accordance with ICAO category 6 and can be raised to category 7 on request. There are always at least three (cat 6) to five (cat 7) employees on firefighting duty. Akureyri International Airport is located in North Iceland, which requires excellent winter services. The airport is very well equipped for snow removal and is open all year round. Further information can be found on: www.isavia.is/en/akureyri-airport



ISAVIA

TECHNICAL INFORMATION

ARP coordinates and site at Aerodrome	65°39'24"N 18°04'19"W Centre of Runway
Direction and distance from the CITY	1.5 NM - 160° GEO
Elevation/Reference temperature	7 FT / 14° C (July)
Geoid undulation at AD ELEV PSN	217 FT
MAG VAR / Annual change	12°W (2019) / 0.27° decreasing
AD Administration, address, telephone, AFS	Isavia Regional Airports. Akureyri Airport Tel.: +354 424 4370 e-mail: biar@isavia.is Control tower Tel: +354 424 4030
Types of traffic permitted	IFR-VFR
Cargo handling facilities	Normal facilities available O/R
Fuel/oil types	AVGAS 100LL, JP-A1 /NIL
Fuelling facilities /capacity	Delivery rate 150 liters per minute AVGAS / Delivery rate 650 liters per minute JP-A1
De-icing facilities	O/R
Hangar space available for visiting aircraft	NIL
Repair facilities for visiting aircraft	Major, light aircraft. Minor, large aircraft
Landing Aids	RWY 01: ILS/RNAV/NDB RWY19: ILS/RNAV/NDB
AD category for fire fighting	CAT VI CAT VII PN 10 min Information tel.: +354 424 4030 e-mail: biar@isavia.is
Runway length, width and strength	2400x45 m /PCN 45 /F/A/X/T
Apron surface and strength	Asphalt 88,5x147 m /PCN 45 /F/A/X/T
Taxiway width, surface and strength	Asphalt 78 m wide /PCN 45 /F/A/X/T
Landing charges	Information on landing charges can be found on: www.isavia.is/en/akureyri-airport
Passenger charges	Information on passenger charges can be found on: www.isavia.is/en/akureyri-airport
Security charges	Information on security charges can be found on: www.isavia.is/en/akureyri-airport
Operational hours	0700 – 2300 Service provided outside of operational hours upon request

RWY designator	APCH LGT type LEN INTST	THR LGT color WBAR	VASIS (MEHT) PAPI	TDZ LGT LEN	RWY Centre line LGT length, spacing color, INTST	RWY edge LGT LEN, spacing color INTST	RWY End LGT color WBAR	SWY LGT LEN (M) color	Remarks
1	2	3	4	5	6	7	8	9	10
01	900 m LIH Crossbar 300 m 9 LDIN flashing lights with 700 m interval Lights start at 7196 m south of RWY 01	green	PAPI 3.5° (53.0 FT) and PAPI 5.3° (180.4 FT)	NIL	NIL	LIH W	RED	NIL	RWY 01: PAPI lights 3.5° left side of RWY PAPI lights 5.3° right side of RWY
19	NIL	green	PAPI 3.5° (59.1 FT)	NIL	NIL	LIH	RED	NIL	TWY-apron LIL B THE ID LGT RWY 01/19 FLG WHITE